L Number	Hits	Search Text	DB	Time stamp
1	1	"20040178997" and impedance\$1	USPAT; US-PGPUB;	2004/09/21 12:01
of the		Ann a see a see a see a see	EPO; JPO; DERWENT;	12:01
2	. 1	"20040178997" and temperature	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/21 12:37
3	1	5053757.pn. and resist\$6	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/21 13:25
4	0	"20040178997" and error and correct\$6	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/21 12:37
5	1	"20040178997" and error	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/21 12:37
6	1	5053757.pn. and gain and error	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/21 13:28
7	1	5053757.pn. and gain and error and (microprocessor or processor or computer)	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/21 13:29
<del>-</del>	22345	touch adj screen	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 08:26
-	1656	touch adj screen and calibration and system	USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20 08:06
-	1315	touch adj screen and calibration and system and plural\$6	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 08:06
<b>-</b>	511	touch adj screen and calibration and system and plural\$6 and terminal\$1	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 08:06
	464	touch adj screen and calibration and system and plural\$6 and terminal\$1 and control\$6 and circuit\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 08:07
_    - 	346	touch adj screen and calibration and system and plural\$6 and terminal\$1 and control\$6 and circuit\$6 and apply\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 08:07

			TYODAM	10004400400
	345	touch adj screen and calibration and	USPAT; US-PGPUB;	2004/09/20 08:07
ļ ļ		system and plural\$6 and terminal\$1 and control\$6 and circuit\$6 and apply\$6 and	EPO; JPO;	00:07
		signal\$6	DERWENT;	i
	,	Signary of the distriction of the state of t	IBM TDB	
- 1	274	touch adj screen and calibration and	USPAT;	2004/09/20
!		system and plural\$6 and terminal\$1 and	US-PGPUB;	08:08
,		control\$6 and circuit\$6 and apply\$6 and	EPO; JPO;	
		signal\$6 and terminal\$1 and sense\$6	DERWENT;	]
			IBM_TDB	1
-	266		USPAT;	2004/09/20
		system and plural\$6 and terminal\$1 and	US-PGPUB; EPO; JPO;	08:08
		control\$6 and circuit\$6 and apply\$6 and signal\$6 and terminal\$1 and sense\$6 and	DERWENT;	
		effect\$5	IBM TDB	1
}	266	,	USPAT;	2004/09/20
	200	system and plural\$6 and terminal\$1 and	US-PGPUB;	08:09
		control\$6 and circuit\$6 and apply\$6 and	EPO; JPO;	1
		signal\$6 and terminal\$1 and sense\$6 and	DERWENT;	ţ .
		effect\$5 and signal\$6 and touch\$6	IBM_TDB	1
-	247	touch adj screen and calibration and	USPAT;	2004/09/20
		system and plural\$6 and terminal\$1 and	US-PGPUB;	08:10
		control\$6 and circuit\$6 and apply\$6 and	EPO; JPO;	1
		signal\$6 and terminal\$1 and sense\$6 and	DERWENT; IBM TDB	)
		effect\$5 and signal\$6 and touch\$6 and switch\$6	1011_100	}
	247	touch adj screen and calibration and	USPAT;	2004/09/20
	23,	system and plural\$6 and terminal\$1 and	US-PGPUB;	08:10
		control\$6 and circuit\$6 and apply\$6 and	EPO; JPO;	}
		signal \$6 and terminal \$1 and sense \$6 and	DERWENT;	2
		effect\$5 and signal\$6 and touch\$6 and	IBM_TDB	
		switch\$6 and circuit\$6	******	0004400400
<del>-</del>	247		USPAT;	2004/09/20 08:10
		system and plural\$6 and terminal\$1 and control\$6 and circuit\$6 and apply\$6 and	US-PGPUB; EPO; JPO;	08:10
!		signal\$6 and terminal\$1 and sense\$6 and	DERWENT;	
[		effect\$5 and signal\$6 and touch\$6 and	IBM TDB	
		switch\$6 and circuit\$6 and apply\$6 and		
		calibration		
-	1	touch adj screen and calibration and	USPAT;	2004/09/20
		system and plural\$6 and terminal\$1 and	US-PGPUB;	08:10
}	}	control\$6 and circuit\$6 and apply\$6 and	EPO; JPO;	
		signal\$6 and terminal\$1 and sense\$6 and	DERWENT; IBM TDB	
}	ł	effect\$5 and signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6 and	TBM_TDB	
		calibration and impedence		
_	247	-	USPAT;	2004/09/20
		system and (plural\$6 and terminal\$1) and	US-PGPUB;	08:27
f	{	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	
]	-	and signal \$6 and terminal \$1 and sense \$6	DERWENT;	,
	ļ	and effect\$5) and (signal\$6 and touch\$6	IBM_TDB	
	ļ	and switch\$6 and circuit\$6 and apply\$6)		
}	}	and (calibration and impedence and touch screen)		
] _	1	touch adj screen and calibration and	USPAT;	2004/09/20
1	1	system and (plural\$6 and terminal\$1) and	US-PGPUB;	08:26
	{	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	ì
		and signal\$6 and terminal\$1 and sense\$6	DERWENT;	
Ì	Ì	and effect\$5) and (signal\$6 and touch\$6	IBM_TDB	
(		and switch\$6 and circuit\$6 and apply\$6)		1
{	{	and (calibration and impedence and touch		
		adj screen)	TICDAM -	2004/09/20
-	0	touch adj screen and calibration and	USPAT;	2004/09/20
	}	system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6	US-PGPUB; EPO; JPO;	00.20
}	1	and signal \$6 and terminal \$1 and sense \$6	DERWENT;	
}	1	and effect\$5) and (signal\$6 and touch\$6	IBM TDB	}
Į	1	and switch\$6 and circuit\$6 and apply\$6)		
	1	and (calibration adj impedence and touch		
	l	adj screen)	<u> </u>	
		<u> </u>		

				```
_	0	touch adj screen and calibration adj impedence	USPAT; US-PGPUB; EPO; JPO;	2004/09/20 08:27
s = 0 ,	-1:30 4 · ·	A FAMILIA SA	DERWENT; IBM TDB	
-	1	touch adj screen and calibration and impedence	USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20 08:27
	247	touch adj screen and calibration and system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6 and signal\$6 and terminal\$1 and sense\$6 and effect\$5) and (signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6)	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:28
-	1	and calibration touch adj screen and calibration and system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6 and signal\$6 and terminal\$1 and sense\$6 and effect\$5) and (signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 10:34
	105	and impedence) touch adj screen and calibration and system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6 and signal\$6 and terminal\$1 and sense\$6 and effect\$5) and (signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6 and (resistive or capacitive or inductive) and load)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:35
-	98	touch adj screen and calibration and system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6 and signal\$6 and terminal\$1 and sense\$6 and effect\$5) and (signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6 and calibration and (resistive or capacitive or inductive) and load) and	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:36
-	58	microprocessor touch adj screen and calibration and system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6 and signal\$6 and terminal\$1 and sense\$6 and effect\$5) and (signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6 and calibration and (resistive or capacitive or inductive) and load) and microprocessor and calculate	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:36
	76	touch adj screen and calibration and system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6 and signal\$6 and terminal\$1 and sense\$6 and effect\$5) and (signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6 and calibration and (resistive or capacitive or inductive) and load) and	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:36
	67	microprocessor and calculate\$6 touch adj screen and calibration and system and (plural\$6 and terminal\$1) and (control\$6 and circuit\$6) and (apply\$6 and signal\$6 and terminal\$1 and sense\$6 and effect\$5) and (signal\$6 and touch\$6 and switch\$6 and circuit\$6 and apply\$6 and calibration and (resistive or capacitive or inductive) and load) and microprocessor and calculate\$6 and measurement	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/09/20 08:37

			· · · · · · · · · · · · · · · · · · ·	
-	59	touch adj screen and calibration and	USPAT;	2004/09/20
		system and (plural\$6 and terminal\$1) and	US-PGPUB;	08:37
		(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	
		and signal\$6 and terminal\$1 and sense\$6	DERWENT;	
		and effect\$5) and (signal\$6 and touch\$6	IBM TDB	A TO BANK TO A TO THE
	•	and switch\$6 and circuit\$6 and apply\$6	_	
		and calibration and (resistive or		
	<b>[</b>	capacitive or inductive) and load) and		
	Ì	microprocessor and calculate\$6 and		
	j	measurement and error and applicat\$6		
_	59		USPAT;	2004/09/20
ł	1	system and (plural\$6 and terminal\$1) and	US-PGPUB;	10:35
		(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	
	l	and signal\$6 and terminal\$1 and sense\$6	DERWENT;	
	}	and effect\$5) and (signal\$6 and touch\$6	IBM TDB	
	1	and switch\$6 and circuit\$6 and apply\$6		ł
	1	and calibration and (resistive or		
		capacitive or inductive) and load) and		1
		microprocessor and calculate\$6 and		Ì
	}	measurement and error and (applicat\$6 and		}
	1	calibration and (resistive or capacitive		
	1	or inductive) and load) and respons\$6 and		}
(	1			{
	1	touch	Henau.	2004/09/20
-	0	touch adj screen and calibration and	USPAT;	08:51
1	}	system and (plural\$6 and terminal\$1) and	US-PGPUB;	00.51
	1	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	
	1	and signal\$6 and terminal\$1 and sense\$6	DERWENT;	j
	1	and effect\$5) and (signal\$6 and touch\$6	IBM_TDB	1
Ì		and switch\$6 and circuit\$6 and apply\$6		
		and calibration and (resistive or		1
ł		capacitive or inductive) and load) and		
1	1	microprocessor and calculate\$6 and		
1	}	measurement and error and (applicat\$6 and	ŀ	1
		calibration and (resistive or capacitive		1
		or inductive) and load) and respons\$6 and	}	
ļ		touch\$6 and apply\$6 and measurement and		Ì
}		error and obtian\$6 and correct\$6 and		
		touch and position and measured and touch		
1		and position		
-	1	touch adj screen and calibration and	USPAT;	2004/09/20
	1 ′	system and (plural\$6 and terminal\$1) and	US-PGPUB;	08:50
}	ł	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	}
1		and signal \$6 and terminal \$1 and sense \$6	DERWENT;	j
)	1	and effect\$5) and (signal\$6 and touch\$6	IBM TDB	
1	l	and switch\$6 and circuit\$6 and apply\$6		
	1	and calibration and (resistive or	}	
		capacitive or inductive) and load) and	}	
}		microprocessor and calculate\$6 and		}
1		measurement and error and (applicat\$6 and		00
1		calibration and (resistive or capacitive		
1	1 .	or inductive) and load) and respons\$6 and		1
1	1	touch\$6 and apply\$6 and measurement adj		1
}	}	error and obtain\$6 and correct\$6 and		1
}	}	touch adj position and measured and touch		1
1	1	adj position	}	1
1_	1	1	USPAT;	2004/09/20
1	1	system and (plural\$6 and terminal\$1) and	US-PGPUB;	08:51
1	1	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	,
1	1	and signal \$6 and terminal \$1 and sense \$6	DERWENT;	
1		and signals and terminals and senses and effect\$5) and (signal\$6 and touch\$6	IBM TDB	
	1	and switch\$6 and circuit\$6 and apply\$6	1	*
		1	1	
	}			
		and calibration and (resistive or	1	Į.
		capacitive or inductive) and load) and		
		capacitive or inductive) and load) and microprocessor and calculate\$6 and		
		capacitive or inductive) and load) and microprocessor and calculate\$6 and measurement and error and (applicat\$6 and		
		capacitive or inductive) and load) and microprocessor and calculate\$6 and measurement and error and (applicat\$6 and calibration and (resistive or capacitive		
		capacitive or inductive) and load) and microprocessor and calculate\$6 and measurement and error and (applicat\$6 and calibration and (resistive or capacitive or inductive) and load) and respons\$6 and		
		capacitive or inductive) and load) and microprocessor and calculate\$6 and measurement and error and (applicat\$6 and calibration and (resistive or capacitive		

		i li li and	USPAT;	2004/09/20
-	57	touch adj screen and calibration and system and (plural\$6 and terminal\$1) and	US-PGPUB;	10:35
	Ì	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	10.55
	1	and signal\$6 and terminal\$1 and sense\$6	DERWENT;	ł
— jes	esiment glove, a god	and effect\$5) and (signal\$6 and touch\$6	IBM TDB	and the second of the second of the
		and switch\$6 and circuit\$6 and apply\$6		İ
	ì	and calibration and (resistive or		
	i	capacitive or inductive) and load) and		
	i	microprocessor and calculate\$6 and		
	l	measurement and error and (applicat\$6 and		
ľ	!	calibration and (resistive or capacitive		
ļ	1	or inductive) and load) and respons\$6 and		
	ĺ	touch\$6 and apply\$6 and measurement and		
	[	error and obtain\$6 and correct\$6 and		
	(	touch and position and measured and touch		
		and position	****	0004/00/00
_	19424	touch adj screen and display	USPAT;	2004/09/20
,			US-PGPUB;	08:54
}			EPO; JPO; DERWENT;	
)	ı		IBM TDB	
_	711	touch adj screen and display and	USPAT;	2004/09/20
-	711	(plural\$6 and terminal\$1) and (control\$6	US-PGPUB;	08:55
		and circuit\$6) and (apply\$6 and signal\$6	EPO; JPO;	1.0.00
		and terminal\$1 and sense\$6 and effect\$5)	DERWENT;	
)		and (signal \$6 and touch \$6 and switch \$6	IBM TDB	
)		and circuit\$6 and apply\$6)	_	
_	105	touch adj screen and display and	USPAT;	2004/09/20
		(plural\$6 and terminal\$1) and (control\$6	US-PGPUB;	08:56
		and circuit\$6) and (apply\$6 and signal\$6	EPO; JPO;	
		and terminal\$1 and sense\$6 and effect\$5)	DERWENT;	l l
		and (signal \$6 and touch \$6 and switch \$6	IBM_TDB	l l
		and circuit\$6 and apply\$6) and		1
		(calibration and (resistive or capacitive		
	3.05	or inductive) and load) touch adj screen and display and	USPAT;	2004/09/20
_	105	(plural\$6 and terminal\$1) and (control\$6	US-PGPUB;	08:57
'		and circuit\$6) and (apply\$6 and signal\$6	EPO; JPO;	00.57
•		and terminal\$1 and sense\$6 and effect\$5)	DERWENT;	
		and (signal\$6 and touch\$6 and switch\$6	IBM TDB	
		and circuit\$6) and (apply\$6 and	_	
-		calibration and (resistive or capacitive		
]		or inductive) and load)		
_	59		USPAT;	2004/09/20
		(plural\$6 and terminal\$1) and (control\$6	US-PGPUB;	08:57
		and circuit\$6) and (apply\$6 and signal\$6	EPO; JPO;	
		and terminal\$1 and sense\$6 and effect\$5)	DERWENT;	
		and (signal\$6 and touch\$6 and switch\$6	IBM_TDB	
		and circuit\$6) and (apply\$6 and		
		calibration and (resistive or capacitive or inductive) and load) and	[	
1		microprocessor and calculate\$6 and		
		measurement and error		
_	57		USPAT;	2004/09/20
}	}	(plural\$6 and terminal\$1) and (control\$6	US-PGPUB;	09:00
}	}	and circuit\$6) and (apply\$6 and signal\$6	EPO; JPO;	_
l	{	and terminal\$1 and sense\$6 and effect\$5)	DERWENT;	
{		and (signal\$6 and touch\$6 and switch\$6	IBM TDB	
	}	and circuit\$6) and (apply\$6 and	_	
}	(	calibration and (resistive or capacitive	l	
1	{	or inductive) and load) and	{	
{		microprocessor and calculate\$6 and	Ì	
1	ł	measurement and error and (applicat\$6 and	1	
	1	calibration and (resistive or capacitive	{	
	1	or inductive) and load) and respons\$6 and	1	
		touch\$6 and apply\$6 and measurement and	Ì	
	1	error and obtain\$6 and correct\$6 and	1	
1	{	touch and position and measured and touch	1	.
L	İ	and position and calibration and system	L	

	1562	touch adj screen and display and	USPAT;	2004/09/20
	1362	calibration and system	US-PGPUB; EPO; JPO; DERWENT;	09:00
العلاوري والماسية وال	r Turkan (1. ah)	Anna Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo Carlo C	IBM TDB	of part 1
-	0	touch adj screen and display and calibration and system and touch adj postion	USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20 09:00
_	0	touch adj screen and display and calibration and system and touch adj postion and touch\$6 and measure\$6 and impedence	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 09:01
-	0	touch adj screen and display and calibration and system and touch adj position and touch\$6 and measure\$6 and impedence	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 09:02
-	37	touch adj screen and display and calibration and system and touch adj position	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 09:02
-	0	touch adj screen and display and calibration and system and touch adj position and impedence	USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20 09:03
-	14	touch adj screen and display and calibration and system and touch adj position and impedance	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20 09:03
-	9	touch adj screen and display and calibration and system and touch adj position and impedance and microprocessor	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 09:52
-	10	touch adj screen and calibration and system and touch adj position and impedance and microprocessor and error\$1 and correct\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 09:59
-	0	touch adj screen and calibration and system and touch adj position and impedance and microprocessor and (error\$1 and due and environment and temperature and (wear and tear)) and correct\$6	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20
-	0	touch adj screen and calibration and touch adj position and impedance and microprocessor and (error\$1 and due and environment and temperature and (wear and	USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20
	1	tear)) and correct\$6 touch adj screen and calibration and touch adj position and impedance and microprocessor and (error\$1 and due and environment and temperature and (wear or	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20
_	1	tear or old adj age)) and correct\$6 touch adj screen and calibration and touch adj position and (error\$1 and due and environment and temperature and (wear or tear or old adj age)) and correct\$6	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT;	2004/09/20 10:02
	1	touch adj screen and calibration and touch adj position and (error\$1 and due and environment and temperature and (wear or tear or old adj age))	IBM_TDB USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM TDB	2004/09/20 10:03

	1	touch adj screen and display and	USPAT;	2004/09/20
	_	calibrat\$6 and touch adj position and	US-PGPUB;	10:04
		(error\$1 and due and environment and	EPO; JPO;	l l
		temperature and (wear or tear or old adj	DERWENT;	
		rage))	IBM TDB	1 Bunto 3 a 3 a 4
-	1.	touch adj screen and display and	USPAT;	2004/09/20
		calibrat\$6 and touch adj position and	US-PGPUB;	10:04
	1	(error\$1 and environment and temperature	EPO; JPO;	[
	1	and (wear or tear or old adj age))	DERWENT;	
	1		IBM TDB	
l –	22	touch adj screen and display and	USPAT;	2004/09/20
		calibrat\$6 and touch adj position and	US-PGPUB;	10:11
	1	(error\$1 and (environment or temperature	EPO; JPO;	
		or old adj age))	DERWENT;	[
ĺ		3 7,7	IBM TDB	j l
l	22	touch adj screen and calibrat\$6 and	USPAT;	2004/09/20
}	}	touch adj position and (error\$1 and	US-PGPUB;	10:11
j	)	(environment or temperature or old adj	EPO; JPO;	}
1	]	age))	DERWENT;	
			IBM TDB	
_	9	touch adj screen and display and	USPAT;	2004/09/20
		calibrat\$6 and touch adj position and	US-PGPUB;	10:21
1	}	(error\$1 and (environment or temperature	EPO; JPO;	
}		or old adj age)) and correct\$6 and	DERWENT;	j j
		impedance and microprocessor	IBM TDB	
_	100	touch adj screen and calibration and	USPAT;	2004/09/20
		system and (plural\$6 and terminal\$1) and	US-PGPUB;	10:34
1	ł	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	
1	1	and signal\$6 and terminal\$1 and sense\$6	DERWENT;	
ļ	1	and effect\$5) and (signal\$6 and touch\$6	IBM TDB	
		and switch\$6 and circuit\$6 and apply\$6	_	
		and impedance)	·	
l -	40	touch adj screen and calibration and	USPAT;	2004/09/20
ł	1	system and (plural\$6 and terminal\$1) and	US-PGPUB;	10:45
}	1	(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	
1		and signal\$6 and terminal\$1 and sense\$6	DERWENT;	
		and effect\$5) and signal\$6 and touch\$6	IBM_TDB	
		and switch\$6 and circuit\$6 and apply\$6		· ·
		and calibration and impedance and	-	
	1	microprocessor and calculate\$6 and		
		measurement and error and applicat\$6 and	1	1
}	1	calibration and impedance and respons\$6		ļ
1		and touch\$6 and apply\$6 and measurement	1	
]		and error and obtain\$6 and correct\$6 and		
		touch and position and measured and touch		
		and position	TICDAM:	2004/00/20
-	0	touch adj screen and calibration and	USPAT;	2004/09/20
1	1	system and (plural\$6 and terminal\$1) and	US-PGPUB;	10:47
}		(control\$6 and circuit\$6) and (apply\$6	EPO; JPO; DERWENT;	}
}		and signal\$6 and terminal\$1 and sense\$6		
]		and effect\$5) and signal\$6 and touch\$6	IBM_TDB	j
		and switch\$6 and circuit\$6 and apply\$6	i	
1		and calibration and impedance and		
	1	microprocessor and calculate\$6 and		
		measurement and error and applicat\$6 and	}	
		calibration adj impedance and respons\$6	1	
	}	and touch\$6 and apply\$6 and measurement	}	
		adj error and obtain\$6 and correct\$6 and	1	
[		touch adj position and measured and touch	1	
Į	1	adj position	L	l

-	0	touch adj screen and calibration and	USPAT;	2004/09/20
		system and (plural\$6 and terminal\$1) and	US-PGPUB;	10:47
	<b>!</b>	(control\$6 adj circuit\$6) and (apply\$6	EPO; JPO;	
ì		and signal\$6 and terminal\$1 and sense\$6	DERWENT;	
14 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	S 15.1 %	and effect\$5) and signal\$6 and touch\$6	IBM_TDB	lings acasis,
		and switch\$6 adj circuit\$6 and apply\$6		
	[	and calibration and impedance and	ĺ	İ
[	[	microprocessor and calculate\$6 and	[	
		measurement and error and applicat\$6 and	[	
		calibration adj impedance and respons\$6	ļ	İ
	ļ	and touch\$6 and apply\$6 and measurement		
		adj error and obtain\$6 and correct\$6 and	,	
		touch adj position and measured and touch	}	
_	0	adj position touch adj screen and calibration and	USPAT;	2004/00/20
_	, ,		US-PGPUB;	2004/09/20
		system and (plural\$6 and terminal\$1) and (control\$6 adj circuit\$6) and (apply\$6	EPO; JPO;	10:47
	}	and signal\$6 and terminal\$1 and sense\$6	DERWENT;	1
		and effect\$5) and signal\$6 and touch\$6	IBM TDB	}
}		and switch\$6 adj circuit\$6 and apply\$6	TDIT_TDD	
	,	and calibration and impedance and	1	}
}		microprocessor and calculate\$6 and	(	
		measurement and error and applicat\$6 and	(	
	!	calibration adj impedance and respons\$6	(	(
		and touch\$6 and apply\$6 and measurement	{	•
	**	and error and obtain\$6 and correct\$6 and	{	
ĺ	_	touch adj position and measured and touch	}	ļ
		adj position	}	<b>\</b>
	52	touch adj screen and calibration and	USPAT;	2004/09/20
		system and (plural\$6 and terminal\$1) and	US-PGPUB;	12:53
		(control\$6 and circuit\$6) and (apply\$6	EPO; JPO;	]
		and signal\$6 and terminal\$1 and sense\$6	DERWENT;	}
		and effect\$5) and signal\$6 and touch\$6	IBM_TDB	}
		and switch\$6 and circuit\$6 and apply\$6		}
	}	and calibration and impedance and	{	
		microprocessor and calculate\$6 and		
		measurement and error and applicat\$6 and		
	1	calibration and impedance and respons\$6	-	
		and touch		0.004 (0.0 ) = 0
_	1	"20040178997"	USPAT;	2004/09/20
			US-PGPUB;	12:48
	[		EPO; JPO;	
			DERWENT;	
_	0	"20040178007" and mimales and hamming 161	IBM_TDB	2004/00/20
	1	"20040178997" and pural\$6 and terminal\$1	USPAT; US-PGPUB;	2004/09/20 12:48
			EPO; JPO;	12.30
			DERWENT;	}
			IBM TDB	
_	1	"20040178997" and plural\$6 and terminal\$1	USPAT;	2004/09/21
		bosistioss, and braiding and cerutilaria	US-PGPUB;	11:12
			EPO; JPO;	
			DERWENT;	
	1		IBM TDB	-
_	0	"20030067451" and plural\$6 and terminal\$1	USPAT;	2004/09/20
	1	paraty and condition	US-PGPUB;	12:50
	ì		EPO; JPO;	
	Ì	·	DERWENT;	į
	Ì		IBM TDB	
-	l o	"20030067451" and terminal\$1	USPAT;	2004/09/20
	( )		US-PGPUB;	12:50
!	[		EPO; JPO;	
	{	,	DERWENT;	
		1	ſ	1
'	<b>\</b>		I TOM I DD	
_	2	"20030067451"	IBM_TDB USPAT;	2004/09/20
-	2	"20030067451"	-	2004/09/20 12:50
-	2	"20030067451"	USPAT;	1 1
-	2	"20030067451"	USPAT; US-PGPUB;	1 1

		C 506 000	HCDAM	12004/00/22
-	0	6,506,983.pn. and terminal\$1	USPAT; US-PGPUB;	2004/09/20
	j i		EPO; JPO;	12:31
			DERWENT;	
مديدة الجادية والإحداد	r till for growth	The second second expenses of the participation of the second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second second sec	IBM TDB	
_	8	touch adj screen and calibration and	USPAT;	2004/09/20
		system and (plural\$6 adj terminal\$1)	US-PGPUB;	13:22
		21200m and (branatho ad) conminant,	EPO; JPO;	
			DERWENT;	
			IBM TDB	1
_	1	6611257.pn. and plural\$6 adj terminal\$1	USPAT;	2004/09/20
			US-PGPUB;	13:13
	[		EPO; JPO;	
			DERWENT;	<b>{</b>
			IBM_TDB	
-	2	6611257.pn. and terminal\$1	USPAT;	2004/09/20
		·	US-PGPUB;	13:17
			EPO; JPO;	
	[		DERWENT;	
		CC110E7 we and malik	IBM_TDB	2004/00/20
	1	6611257.pn. and calibration	USPAT;	2004/09/20
	j i		US-PGPUB; EPO; JPO;	15:25
			DERWENT;	
	}		IBM TDB	
_	2	touch adj screen and calibration adj	USPAT;	2004/09/20
		system and (plural\$6 adj terminal\$1)	US-PGPUB;	13:23
	1	-10-20m min (brancht and sepuriment)	EPO; JPO;	
	1		DERWENT;	
			IBM TDB	
~	5	touch adj screen adj calibration adj	USPAT;	2004/09/20
,	[	system	US-PGPUB;	13:37
	}		EPO; JPO;	
	l		DERWENT;	
	{	<u> </u>	IBM_TDB	
-	4	,	USPAT;	2004/09/20
	1	system and terminal\$1	US-PGPUB;	13:38
	1		EPO; JPO;	
	1		DERWENT;	
_	o	5053757.pn. and calibration	IBM_TDB USPAT;	2004/09/20
		5005757.pm. and carried ton	US-PGPUB;	15:23
	1		EPO; JPO;	15.25
			DERWENT;	1
			IBM TDB	
_	О	5053757.pn. and calibrat\$6 adj system	USPAT;	2004/09/20
	1		US-PGPUB;	15:24
			EPO; JPO;	
	]		DERWENT;	
			IBM_TDB	
~	1	5053757.pn. and calibrat\$6	USPAT;	2004/09/21
	1	*	US-PGPUB;	12:21
	1		EPO; JPO;	
}			DERWENT;	
}	1	CC11257	IBM_TDB	2004/00/20
_	0	6611257.pn. and control adj circuit	USPAT;	2004/09/20
	1		US-PGPUB;	15:25
	1		EPO; JPO;	
	,		DERWENT; IBM TDB	
_	0	6611257.pn. and control\$6 adj circuit\$1	USPAT;	2004/09/20
,	1	don't be a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control of a control	US-PGPUB;	15:26
!	1		EPO; JPO;	20.20
	ł		DERWENT;	
			IBM TDB	
_	1	6611257.pn. and control\$6 and circuit\$1	USPAT;	2004/09/20
	1		US-PGPUB;	15:27
	1		EPO; JPO;	
[	1		DERWENT;	
	1		IBM_TDB	
<u> </u>	<u> </u>	<u> </u>	L	

-	1	6611257.pn. and control\$6 a and impedance	nd circuit\$1	USPAT; US-PGPUB; EPO; JPO;	2004/09/20 15:27	
		encolore description to the first of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of the control of	unit of the state of the	DERWENT; IBM_TDB	Let 1. 1985 Mark His	

Search History 9/21/04 1:53:41 PM Page 10